

Type F-2 / F-3 ISO-EXTRA

Plug valves with full bore design



Type ISO-EXTRA

Full bore plug valves



- Flange connections
- 2-way up to 3-way

DN 15 - 600 / PN 10 - 100
NPS ½ - 24 / Class 150 - 600
(higher pressure: type HDS)

Range of application:
-60 < T < 230/320°C
vacuum-capable

EXTRA design

- minimal pressure drop:
K_{vs}-value similar to straight pipe
- body suitable for abrasive media
- no clogging of crystallizing or polymerizing media

Design characteristics

- easy accessible adjustment of the plug
- PED 2014/68/EU
- low fugitive emission in line with TA LUFT, ISO 15848 & API 641 requirements
- mounting-flange for actuators acc. to ISO 5211
- Fire-Safe - API 607 / ISO 10497
- SIL 3 certified

Options


- multiport valves
- heating jacket
- oversize design
- flushing device
- FDA compliant
- painting
- oil and grease-free assembly
- piggable (type ISO-EXTRA-M)

Recommendation for high torques:
AZ actuator **type AIR-GEAR**



PT diagram, plug types, sealing systems, material selection: see catalogue part ENGINEERING

Flange dimensions acc. to DIN EN / ASME




DIN EN 1092-1									DIN EN 1092-1								
DN	PN	øD [mm]	flange bore [mm]	øk no.	Ø [mm]	øg [mm]	b [mm]	f [mm]	DN	PN	øD [mm]	flange bore [mm]	øk no.	Ø [mm]	øg [mm]	b [mm]	f [mm]
15	10-40	95	65	4	14	45	16	2	125	10-16	250	210	8	18	188	22	3
20	10-40	105	75	4	14	58	18	2	125	25-40	270	220	8	26	188	26	3
25	10-40	115	100	4	14	68	18	2	150	10-16	285	240	8	22	212	22	3
32	10-40	140	100	4	18	78	18	2	150	25-40	300	250	8	26	218	28	3
40	10-40	150	110	4	18	88	18	2	200	10-16	340	295	8/12	22	268	24	3
50	10-40	165	125	4	18	102	20	3	25 40	360 375	310 320	12 26 30	278 285	30 34	3	3	
65	10-16	185	145	4	18	122	22	3	250	10 16	395 405	350 355	12	22 26	320	26	3
	25-40	185	145	8	18	122	22	3	250	25 40	425 450	370 385	12	30 33	335 345	32 38	3
80	10-40	200	160	8	18	138	24	3	300	10 16	445 460	400 410	12	22 26	370 378	26 28	4
100	10-16	220	180	8	18	158	20	3	300	25 40	485 515	430 450	16	30 33	395 410	34 42	4
	25-40	235	180	22	18	162	24	3	350	10 16	505 520	460 470	12	22 26	430 438	26 30	4
									350	25 40	555 580	490 510	16	33 36	450 465	38 46	4
									400	10 16	565 580	515 525	16	26 30	482 490	26 32	4
									400	25 40	620 660	550 585	16	36 39	505 535	40 50	4
									450	10 16	615 640	565 585	20	26 30	532 550	28 36	4
									450	25 40	670 685	600 610	20	36 39	555 560	46 57	4
									500	10 16	670 715	620 650	20	26 33	585 610	28 38	4
									500	25 40	730 755	660 670	20	36 42	615 615	48 57	4
									600	10 16	780 840	725 770	20	30 36	685 725	30 47	5
									600	25 40	845 890	770 795	20	39 48	720 735	58 72	5

ASME B16.5									ASME B16.5								
NPS	Class	øD [mm]	flange bore [mm]	øk no.	Ø [mm]	øg [mm]	b [mm]	f [mm]	NPS	Class	øD [mm]	flange bore [mm]	øk no.	Ø [mm]	øg [mm]	b [mm]	f [mm]
½	150	90	60,3	4	15,7	34,9	10,0	2	5	150	255	215,9	8	22,3	185,7	24,3	2
	300	95	66,7	4	15,7	34,9	14,7	2	5	300	280	235	8	22,3	185,7	35,4	2
¾	150	100	69,9	4	15,7	42,9	10,9	2	6	150	280	241,3	8	22,3	215,9	25,9	2
	300	115	82,5	4	19,1	42,9	16,3	2	6	300	320	269,9	12	22,3	215,9	37,0	2
1	150	110	79,4	4	15,7	50,8	11,6	2	8	150	345	298,5	8	22,4	269,9	29,0	2
	300	125	88,9	4	19,1	50,8	17,9	2	8	300	380	330,2	12	25,4	269,9	41,7	2
1¼	150	115	88,9	4	15,7	63,5	13,2	2	10	150	405	362	12	25,4	323,8	30,6	2
	300	135	98,4	4	19,1	63,5	19,5	2	10	300	445	387,4	16	28,4	323,8	48,1	2
1½	150	125	98,4	4	15,7	73,0	14,7	2	12	150	485	431,8	12	25,4	381	32,2	2
	300	155	114,3	4	22,3	73,0	21,1	2	12	300	520	450,8	16	31,7	381	51,3	2
2	150	150	120,7	4	19,1	92,1	16,3	2	14	150	535	476,3	12	28,4	412,8	35,4	2
	300	165	127,0	8	19,1	92,1	22,7	2	14	300	585	514,4	20	31,7	412,8	54,4	2
2½	150	180	139,7	4	19,1	104,8	17,9	2	16	150	595	539,8	16	28,4	469,9	37,0	2
	300	190	149,3	8	22,3	104,8	25,9	2	16	300	650	571,5	20	35	469,9	57,6	2
3	150	190	152,4	4	19,1	127	19,5	2	18	150	635	577,9	16	31,8	533,4	40,1	2
	300	210	168,3	8	22,3	127	29,0	2	18	300	710	628,6	24	35	533,4	60,8	2
4	150	230	190,5	8	19,1	157,2	24,3	2	20	150	700	635	20	31,8	584,2	43,3	2
	300	255	200,0	8	22,3	157,2	32,2	2	20	300	775	685,8	24	35	584,2	64	2
									24	150	815	749,3	20	35,1	692,2	48,1	2
									24	300	915	812,8	24	41,1	692,2	70,3	2

Type F-2 / F-3 ISO-EXTRA

Technical information DN 15 - 40 / NPS ½ - 1½



DIN EN 558-1 / ISO 5211	DN	PN	L	L/2	R	H	AZ	SW	torque**	weight	F-2		F-3-S (L)		F-3-W (L4)	
	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	flange	[mm]	[Nm]	[kg]	K _{vs}	C _v	K _{vs}	C _v	K _{vs}	C _v
	15	10-40	130	65	200	102,2	F05	11	30	6,8	19	22	7	8	8	9
	20	10-40	150	75	200	102,2	F05	11	30	7,9	36	42	*	*	*	*
	25	10-40	160	80	320	119	F07	14	80	9,1	70	81	20	24	22	25
	32	10-40	180	90	420	137	F07	19	140	10,1	113	130	34	39	36	42
	40	10-40	200	100	420	145	F10	22	240	13,7	193	223	53	61	57	66
ASME B16.10 / ISO 5211	NPS	Class	L***	L/2	R	H	AZ	SW	torque**		F-2		F-3-S (L)		F-3-W (L4)	
			[mm]	[mm]	[mm]	[mm]	flange	[mm]	[Nm]	[kg]	K _{vs}	C _v	K _{vs}	C _v	K _{vs}	C _v
	½	150	108	54	200	102,5	F05	11	30	4,5	20	23	*	*	*	*
		300	140	70						6,1	18	21	*	*	*	*
	¾	150	117	58,5	200	102,5	F05	11	30	5,2	41	48	*	*	*	*
		300	152	76						6,7	36	42	*	*	*	*
	1	150	160/176	80	320	119	F07	14	80	7,3	70	81	20	24	22	25
		300	230/190	115						8,2	53	62	20	23	21	24
	1¼	150	180/222	90	420	137	F07	19	140	*	113	130	34	39	36	42
		300	260/241	130						*	95	110	33	38	35	41
	1½	150	200	100	420	145	F10	22	240	17,5	193	223	58	61	57	66
		300	260	130						18,2	170	196	52	60	57	66

* on request

** manufacturer recommended sizing torque (incl. 100% safety)

*** available lengths acc. to EN / ASME for 2-way valves (all other data apply to EN versions)

K_{vs} [m³/h] / C_v [US.gal/min] values determined by flow simulation (VDO/VDE 2173, (medium = water 20°C, pressure loss Δp = 1 bar)


Some designs, sizes and/or configurations may be fitted with threaded flange holes.

Higher pressure rating on request.

Specifications for AZ flange (console type), SW, torque and weight apply to F-2.

Type F-2 / F-3 ISO-EXTRA

Technical information DN 50 - 350 / NPS 2 - 14



		L	L/2	E	R	H	I	gear	AZ	SW	torque**	weight	F-2		F-3-S (L)		F-3-W (L4)		
DN	PN	[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	(Pro-Gear)	flange	[mm]	[Nm]	[kg]	K _{VS}	C _V	K _{VS}	C _V	K _{VS}	C _V	
DIN EN 558-1 / ISO 5211	50	10-40	230	115	52,5	300	195	240	Q 400-S	F10	22	350	28	323	374	85	98	90	105
	65	10-40	290	145	68,75	400	243	265	Q 800-S	F12	22	500	41	569	658	143	166	154	179
	80	10-40	310	155	68,75	400	248	365	Q 800-S	F14	27	600	51	947	1095	222	257	233	269
	100	10-40	350	175	137,5	600	270	365	Q 6500-S	F16	55	2000	111	1446	1672	338	391	361	417
	150	10-40	480	240	137,5	600	315	365	Q 6500-S	F25	□55	4000	199	3338	3859	775	895	816	943
	200	10-40	600	300	180	700	355	520	Q 12000-S	F25	□55	6500	359	6362	7356	1385	1601	1470	1698
	250	10-40	730	365	180	700	385	520	Q 12000-S	F30	□75	8500	533	10346	11961	2166	2504	2285	2642
	300	10-40	850	425	252,5	700	460	600	Q 24000-S	F30	□75	19500	923	15316	17707	3141	3631	3312	3829
	350	10-40	980	490	252,5	700	495	600	Q 32000-S	F30	□75	25000	1409	21195	24504	4294	4964	4540	5249
	400	10-40	1100	550	*	700	535	600	Q 32000-S	F35	*	29000	*	28438	32878	5608	6484	5989	6923
	450	10-40	1200	600	*	700	620	600	Q 50000-S	F40	*	31000	*	37079	42867	7057	8158	7667	8864
500	10-40	1250	625	*	700	640	740	Q 50000-S	F40	*	33000	*	47672	55113	8890	10278	9442	10916	
600	10-40	1450	725	*	*	*	*	*	F48	*	*	2596	71299	82429	12646	14620	13439	15537	
NPS Class		L***	L/2	E	R	H	I	gear	AZ	SW	torque**	weight	F-2		F-3-S (L)		F-3-W (L4)		
		[mm]	[mm]	[mm]	[mm]	[mm]	[mm]	(Pro-Gear)	flange	[mm]	[Nm]	[kg]	K _{VS}	C _V	K _{VS}	C _V	K _{VS}	C _V	
ASME B16.10 / ISO 5211	2	150	230/222	115	*	300	195	240	Q 400-S	F10	22	350	34	323	374	85	98	90	105
	300	300/241	150	*	300	195	240	Q 400-S	F10	22	350	37	282	327	83	96	89	102	
	2½	150	290/298	145	*	400	243	265	Q 800-S	F12	22	500	40	569	658	143	166	154	179
	300	290/330	145	*	400	243	265	Q 800-S	F12	22	500	43	569	658	143	166	154	179	
	3	150	310/343	155	*	400	243	265	Q 800-S	F14	27	600	56	947	1095	222	257	233	269
	300	310/397	155	*	400	243	265	Q 800-S	F14	27	600	60	947	1095	222	257	233	269	
	4"	150	350/432	175	137,5	600	270	365	Q 6500-S	F16	55	2000	*	1446	1672	338	391	360	416
	300	430/457	215	137,5	600	270	365	Q 6500-S	F16	55	2000	*	1317	1522	335	384	358	414	
	6	150	480/546	240	137,5	600	315	365	Q 6500-S	F25	□55	4000	191	3338	3859	781	903	820	948
	300	550/559	275	137,5	600	315	365	Q 6500-S	F25	□55	4000	210	3155	3647	768	888	815	943	
	8	150	600/622	300	180	700	355	520	Q 12000-S	F25	□55	6500	314	6362	7356	1385	1601	1470	1699
	300	650/686	300	180	700	355	520	Q 12000-S	F25	□55	6500	*	6108	7062	1388	1605	1466	1695	
	10	150	730/660	365	180	700	385	520	Q 12000-S	F30	□75	8500	*	10344	11959	1934	2235	2299	2658
	300	775/826	365	180	700	385	520	Q 12000-S	F30	□75	8500	544	9933	11483	1941	2244	2327	2690	
	12	150	850/762	425	252,5	700	460	600	Q 24000-S	F30	□75	19500	924	15317	17708	3064	3543	3308	3825
300	850/965	425	252,5	700	460	600	Q 24000-S	F30	□75	19500	963	15317	17708	3064	3543	3308	3825		
14	150	980/*	490	252,5	700	495	600	Q 32000-S	F30	□75	25000	*	21194	24503	4285	4954	4545	5255	
16	150	838	550	*	700	535	600	Q 32000-S	F35	*	29000	1438	32823	37947	5638	6518	5991	6927	
18	300	1200	600	*	700	620	600	Q 50000-S	F40	*	31000	2242	37078	42866	7067	8170	7667	8864	
20	300	991	625	*	700	640	740	Q 50000-S	F40	*	33000	2382	54544	63058	8996	10400	9495	10977	
24	300	1450	725	*	*	*	*	*	F48	*	*	*	71301	82431	12489	14439	13439	15537	

* on request

** manufacturer recommended sizing torque (incl. 100% safety)

*** available lengths acc. to EN / ASME for 2-way valves (all other data apply to EN versions)

K_{VS} [m³/h] / C_V [US.gal/min] values determined by flow simulation (VDO/VDE 2173, (medium = water 20°C, pressure loss Δp = 1 bar)

Some designs, sizes and/or configurations may be fitted with threaded flange holes.

Higher pressure rating on request.

Specifications for AZ flange (console type), SW, torque and weight apply to F-2.

AZ-plug valve: the design principle

Key advantages

- free of cavities
- no contamination of process media
- adjustability of the plug and sealings
- maintenance-free due to self-lubricating and chemical-resistant PTFE-sleeve
- low emission design
- constant torque (Δp independent !)
- vacuum-capable

Tapered plug

- plug pressed into the PTFE-sleeve
- polished surface



Body

- tapered body interior
- integrated supporting ribs avoid rotation and coldflow of the sleeve
- large sealing surface







PTFE-sleeve

- mechanically locked into the valve body
- complete PTFE chambering
- robust, one-piece sleeve covers and protects the entire plug



Cavity-free: suitable for all media

Technical comparison

AZ-plug valve	Ball valve
<p>Soft seated plug valve with PTFE-sleeve</p>  <p>Main sealing components</p> <ul style="list-style-type: none"> • metallic plug • sleeve 	<p>Soft seated ball valve with PTFE sealing rings, floating ball</p>  <p>Main sealing components</p> <ul style="list-style-type: none"> • metallic ball • sealing rings
OPEN position	
<ul style="list-style-type: none"> • suitable for all media due to cavity-free design • sealing surfaces are completely protected  <p>free of cavities</p>	<ul style="list-style-type: none"> • critical for the following media due to design with cavities <ul style="list-style-type: none"> ○ corrosives: crevice corrosion ○ polymerizing: clogging ○ crystallizing: abrasion / clogging  <p>cavities</p> <p>cavities</p>
During operation	
<ul style="list-style-type: none"> • free of cavities, media cannot settle or be trapped • solids are pushed away • no contamination with old media 	<ul style="list-style-type: none"> • with cavities, media can settle or be trapped • solids cause abrasion of the sealing rings • contamination of process media  <p>Damage of the sealing rings</p>

Safe and reliable tightness for years

Adjustable




- tapered plug design allows retightening of the sealing on site - if needed
- adjusting bolt even accessible with mounted actuator / gearbox

Several sealings to atmosphere

- 1 Primary: sleeve
- 2 Secondary: V-diaphragm/cover seal
- 3 Tertiary: stem packing (optional)



Detailed information about all certified AZ cover & stem sealing systems see chapter SEALING SYSTEMS



ISO cover



- pressure containing cover bolts separated from bracket boltings
- cover and bracket acc. to ISO 5211 for efficient actuator / gearbox assembly


Reduced and full bore design

Execution

Reduced bore

Type STANDARD


- compact valve (FF / weight)
- optimal torques for economic automation



Full round bore

Type EXTRA

- maximum flow rate
- minimal pressure drop
- piggable (optional)




Type ISO-EXTRA

- excellent for abrasive, slurry and solid-containing applications
- maximum flow rate compared to other valve types with the same nominal size



Maximum flow rate



Options



Multi-port

- whole range of multi-port plugs for all configurations (up to 7-way)
- horizontal and vertical installation



Vented options

- plug bottom
- plug upstream / downstream automatic pressure balance in case of thermal media expansion



System requirements

- **FDA** = Food and Drug Administration certifications and compliant materials
- **GMP** = Good-Manufacturing-Practice
- **CIP** = Clean-in-Place
- Polished internal surfaces, surface finish $<0.8 \text{ Ra } \mu\text{m}$ ($<32 \text{ Ra } \mu\text{in}$)
- oil and grease free
- water-free



All connections possible

- flanges acc. to DIN, ASME, JIS etc.
- welded ends
- screwed and threaded ends
- combinations of connections
- oversize flanges
- compression fittings and ferrule ring couplings
- special connections




High and low temperature

- extended bonnet with sealing at the top
- stem extension for insulated valves




Modular operation concept

Bracket according to ISO 5211

- standard installation of gearbox and actuator
- safe due to independent mounting of cover and bracket
- covering bonnet bolts to prevent opening of valve in service
- precise centering of the bracket to the plug stem due to adjusting ring
- easy inline plug adjustment during the process, screws are always accessible






Cover and stem sealing systems suitable for general applications

Type STANDARD			
	<ul style="list-style-type: none"> ● plug adjustment ● thrust collar ● cover sealing (PTFE) ● stainless steel diaphragm ● Secondary sealing: V-diaphragm (PTFE), delta thrust collar (PTFE) ● Primary sealing: sleeve* 		
	Type FS2 Fire-Safe-sealing (API 607)		
		<ul style="list-style-type: none"> ● plug & packing adjustment ● Tertiary sealing: Packing to atmosphere (graphite) ● thrust collar ● cover sealing (graphite) ● stainless steel diaphragm ● Secondary sealing: V-diaphragm (PTFE) and delta thrust collar (PTFE) ● Primary sealing: sleeve* 	
		Type CA2 Chemistry sealing	
			<ul style="list-style-type: none"> ● plug & packing adjustment ● Tertiary sealing: Packing to atmosphere (PTFE) ● thrust collar ● cover sealing (PTFE) ● stainless steel diaphragm ● Secondary sealing: V-diaphragm, delta thrust collar (PTFE) ● Primary sealing: sleeve*

*) The sleeve material has a decisive influence on the maximum operating temperature
Material selection acc. to PT-diagram

More safety for severe applications

*engineered.
fast.
dynamic.*

Type FSN	Fire-Safe-sealing (API 607)
<p>plug adjustment ●</p> <p>triple safety stem packing adjustment ●</p> <p>Tertiary sealing: triple safety stem packing (graphite) ●</p> <p>Secondary sealing: V-diaphragm (PTFE) and delta thrust collar (PTFE) ●</p> <p>cover sealing (graphite) ●</p> <p>Primary sealing: sleeve* ●</p>	
<p>Type FSN-EF</p> <p>Emission Free</p> <p>plug adjustment ●</p> <p>triple safety stem packing adjustment ●</p> <p>Quaternary sealing: three o-rings at the stem ●</p> <p>Tertiary sealing: triple safety stem packing ●</p> <p>Secondary sealing: V-diaphragm (PTFE) and delta thrust collar (PTFE) ●</p> <p>cover sealing (graphite) ●</p> <p>Primary sealing: sleeve* ●</p>	<p>NEW!</p> 
<p>Type FSN-SL</p> <p>live-loaded</p> <p>plug adjustment ●</p> <p>o-rings protect the springs against corrosion ●</p> <p>triple safety stem packing adjustment ●</p> <p>disk springs (optionally made of Inconel) ●</p> <p>Tertiary sealing: triple safety stem packing (graphite) ●</p> <p>Secondary sealing: V-diaphragm (PTFE) and delta thrust collar (PTFE) ●</p> <p>cover sealing (graphite) ●</p> <p>Primary sealing: sleeve* ●</p>	

*) The sleeve material has a decisive influence on the maximum operating temperature
Material selection acc. to PT-diagram

Material for **type CASN** and **CASN-SL** chemistry safety sealing: packing and cover sealing in PTFE

Special sealing systems

Chevron packing

- increases the contact pressure (when pressure builds up on the safety stem packing towards plug stem)
- for toxic and fugitive media
- high wear resistance



Type CL Chlorine / gas applications

- approved for chlorine applications and other toxic gases
- ideal for media with changing state of aggregate (e.g. liquid to gas, vice versa)
- vacuum capable



Detection ports for monitoring purpose of lethal gases (phosgene, etc.)

- detection ports for early recognition of potential leakages
- sniffing at sealing surfaces to atmosphere

- stem packing
- cover sealing
- flange sealing




Cover and stem sealing systems for lined plug valves

*engineered.
fast.
dynamic.*

Type CA 2A **Chemistry sealing**

NEW!


- plug & packing adjustment ●
- stem O-ring ●
- Tertiary sealing:** O-ring (FKM / FFKM) ●
- thrust collar ●
- stainless steel diaphragm ●
- Secondary sealing:** V-diaphragm & delta thrust collar (PTFE) ●
- Primary sealing:** lined body ●



Type SAFE-LINED **Chemistry sealing**

lined cover


- plug adjustment ●
- triple safety stem packing adjustment ●
- Tertiary sealing:** ●
- triple safety stem packing (PTFE) to atmosphere ●
- Secondary sealing:** V-diaphragm (PTFE), delta thrust collar (PTFE) ●
- lined cover ●
- Primary sealing:** lined body* ●



Type SAFE-LINED-SL **Chemistry sealing**

live-loaded

- plug adjustment ●
- o-rings protect the springs against corrosion ●
- triple safety stem packing adjustment ●
- disk springs (optionally made of Inconel) ●
- Tertiary sealing:** ●
- triple safety stem packing (PTFE) to atmosphere ●
- Secondary sealing:** V-diaphragm (PTFE), delta thrust collar (PTFE) ●
- lined cover ●
- Primary sealing:** lined body* ●



*) Lining and plug material have a decisive influence on the maximum operating temperature
Material selection according to PT-diagram.

WORLD'S FIRST EMISSION FREE
plug valve certified acc. to **ISO 15848-1 / AH**
Type **FSN-EF**

NEW!



Fugitive
Emissions



Low-Emission according ISO 15848, TA-Luft & API 641



For all important information about ISO 15848, TA-Luft & API 641, as well as the current certificates, please refer to the "AZ Fugitive Emission" brochure



Latest information about ISO 15848 / API 641 / TA Luft see AZ Fugitive Emissions leaflet



Casting materials




Material Group	Common Name	Casting Material					
		EN / DIN	Short name	Material-No.	ASTM	Grade	UNS
Carbon Steel / Ductile Iron							
Ductile Iron	SG Iron	EN 1563	EN-GJS-400-18-LT	5.3103	A395	-	F32800
Carbon Steel	CS	EN 10213	GP240GH	1.0619	A216	WCB	J03002
Low Temp. Carbon Steel	LTCS	EN 10213	G17Mn5	1.1131	A352	LCB	J03003
Low Temp. Carbon Steel	LTCS	EN 10213	G21Mn5	1.1138	A352	LCC	J02505
Stainless Steel							
Stainless Steel	Duplex 2205	EN 10213	GX2CrNiMoN22-5-3(4A)	1.4470	A995	4A-CD3MN	J92205
Stainless Steel	Duplex 1B	EN 10213	GX3NiCrMoCuN26-6-3-3	1.4517	A995	1B-CD4MCuN	J93372
Austenitic	SS	EN 10213	GX5CrNi19-10	1.4308	A351	CF8	J92600
Austenitic	SS	EN 10213	GX2CrNi19-11	1.4309	A351L	CF3	J92700
Austenitic	SS	EN 10213	GX5CrNiMo19-11-2	1.4408	A351	CF8M	J92900
Austenitic	SS	EN 10213	GX2CrNiMo19-11-2	1.4409	A351	CF3M	J92800
Super Austenitic	Alloy 20	EN 10213	NiC420CuMo	1.4500	A351	CN7M	N08007
Super Austenitic	Alloy 20 mod.	EN 10213	GX2NiCrMoCuN25-20	1.4536	A743	CN7MS	J94650
Super Austenitic	AL6XN	-	-	-	A351	CN3MN	J94651
Superduplex	Superduplex 5A	EN 10213	25Cr-7Ni-Mo-N	1.4469	A995	CE3MN	J93404
Nickel Alloy							
	Monel/Alloy400	DIN 17730	G-NiCu30 Nb	2.4365	A494	M35-1	N24135
	Hastelloy C mod.	-	-	-	A494	CW6M	N30107
	Hastelloy C	-	-	2.4537	A494	CW12MW	N30002
	Hastelloy C-276	-	-	2.4883	-	-	-
	Hastelloy B-3	-	-	-	-	-	-
	Inconel 600	-	-	-	A494	CY40	N06040
	Inconel 625	-	-	-	A494	CW6MC	N26625
	Inconel 825	-	-	-	A494	CU5MCuC	N08826
	Nickel	DIN 17730	G-Ni 95	2.4170	A494	CZ100	N02100
Other Material Groups							
Tantalum	Tantalum	-	-	-	-	-	-
Titanium	Ti 2	DIN 17865	G-Ti 2	3.7031	B367	C-2	R52550
Zirconium	Zirconium 702	-	-	-	B752	702C	-
Zirconium	Zirconium 705	-	-	-	-	705C	-

All rights reserved, all indications without engagement, subject to modifications.

The use of these equivalents has to be evaluated on a case-by-case basis.

Other materials on request.

Equivalent forged and bar-stock materials



Common Name	Mat.Nr.	Grade	Similar Forged Material						Bar Material	
			EN / DIN	Short Name	Mat.Nr.	ASTM	Grade	UNS	ASTM Short	
Carbon Steel / Ductile Iron										
SG Iron	5.3103	-	EN 1563	EN-GJS-400-18-LT	5.3103	A395-99	60-40-18	-	-	-
CS	1.0619	WCB	EN 10213	GP240GH	1.0619	A105	A105	-	-	-
LTCS	1.1131	LCB	-	-	-	A350	LF2-Class1	G10300	-	-
LTCS	1.1138	LCC	-	-	1.0566	A350	LF2-Class1	G10250	-	-
Stainless Steel										
Duplex 2205	1.4470	4A-CD3MN	EN 10028-7	X2CrNiMoN22-5-3	1.4462	A182	F51	S32205	A479	S31803
Duplex 1B	1.4517	1B-CD4MCuN	EN 10028-7	X2CrNiMoCuN25-5-3	1.4507	A182	F59	S32520	A479	S32550
SS	1.4308	CF8	EN 10028-7	X5CrNi18-10	1.4301	A182	F304	S30400	A276	304
SS	1.4309	CF3	EN 10028-7	X2CrNi19-11	1.4306	A182	F304L	S30403	A276	304L
SS	1.4408	CF8M	EN 10028-7	X5C4NiMo17-12-2	1.4401	A182	F316	S31600	A276	316
SS	1.4409	CF3M	EN 10028-7	X2CrNiMo 17-12	1.4404	A182	316L	S31603	A276	316L
Alloy 20	1.4500	CN7M	-	-	2.4660	B462	N08020	N08020	B473	N08020
Alloy 20 mod.	1.4536	CN7MS	-	-	-	-	-	-	-	-
AL6XN	-	CN3MN	EN 10028-7	X1NiCrMoCuN25-20-7	1.4529	A182	F62	N08367	B462	N08367
Superduplex 5A	1.4469	CE3MN	EN 10028-7	X2CrNiMoN25-7-4	1.4410	A182	F63	S32615	-	-
Nickel Alloy										
Monel/Alloy400	2.4365	M35-1	DN 17744	NiCu30Fe	2.4360	B165	Alloy 400	N04400	B164	N04400
Hastelloy C mod.	-	CW6M	-	-	-	A494	-	-	-	-
Hastelloy C	-	CW12MW	-	NiMo16CrW	-	A494	-	-	-	-
Hastelloy C-276	-	-	DIN 17744	NiMo16Cr15W	2.4819	B565	N10675	N10276	B574	N10276
Hastelloy B-3	-	-	DIN 17744	NiMo29Cr	2.4600	B565	N10675	N10675	B335	N10675
Inconel 600	-	CY40	DIN 17742	NiCr15Fe	2.4816	B565	N06600	N06600	B166	N06600
Inconel 625	-	CW6MC	DIN 17744	NiCr22Mo9Nb	2.4856	B565	N06625	N06625	B446	N06625
Inconel 825	-	CU5MCuC	DIN 17744	NiCr21Mo	2.4858	B564	N08825	N08825	B425	N08825
Nickel	2.4170	CZ100	-	-	-	-	-	-	B160	N02200
Other Material Groups										
Tantalum	-	-	-	-	-	B365	TaW2,5	R05252	-	-
Ti 2	3.7031	C-2	DIN 17864	Grade 2	3.7035	B381	F2	R50400	B348	Grade 2
Zirconium 702	-	702C	-	-	6.0702	B493	R60702	R60702	B550	R60702
Zirconium 705	-	705C	-	-	-	B493	R60705	R60705	B550	R60705

All rights reserved, all indications without engagement, subject to modifications.

The use of these equivalents has to be evaluated on a case-by-case basis.

Other materials on request.

Lining materials



Lining materials

The high density, extremely resistant lining is at least 3 mm thick. New granulate is used exclusively, no refurbished regenerates or similar materials.

Fluoropolymer lining materials

- Body: PFA, PFA conductive and FEP
- Plug: PTFE, PFA, PFA conductive and FEP

body lining	Combination of linings plug lining	T _{max}
PFA	PTFE ¹⁾ or special materials	210°C / 410°F
PFA	PFA	200°C / 392°F
PFA	FEP	150°C / 302°F
PFA conductive	PFA conductive	125°C / 257°F
FEP	FEP	150°C / 302°F
FEP	PFA	150°C / 302°F

- 1) Plugs with PTFE lining only for two-way valves up to DN 100.
Plugs for multi-way valves not with PTFE lining available.

IMPORTANT NOTE

For demanding conditions, such as process temperatures exceeding 150°C / 302°F: Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of lining material, cover sealing type and special features.

Sleeve materials



Category	Sleeve Material	Characteristics	Typical applications	T _{MAX}
PTFE	PTFE, virgin	low friction, very good sealing characteristic	standard sleeve material for most applications	230°C / 446°F
RPTFE	PTFE-Glass	reinforced PTFE	additional stability for multiway valves with horizontal ports	230°C / 446°F
	PTFE-Graphite	reinforced PTFE	high temperature applications	250°C / 482°F
modified PTFE	TFM 1600* NXT 75* M 111*	chemically modified PTFE, reduced permeation, low friction	chemical applications where reduced permeability compared to PTFE is required	250°C / 482°F
Special Sleeves	PTFE-P* NFCE* NCS*	high performance sleeve materials	severe service highest temperatures, high pressure, abrasive applications	320°C / 608°F
PFA	PFA	reduced permeation	chemical applications where reduced permeability compared to PTFE is required	200°C / 392°F
UHMW-PE	UHMW-PE	Ultra High Molecular Weight Polyethylene	radiation resistant, abrasive application	80°C / 176°F


*) sleeve material selection depending on availability at AZ manufacturing site

IMPORTANT NOTE

for demanding conditions, such as process temperatures exceeding 200°C / 392°F:
Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of sleeve material, cover sealing type and special features. For other sleeve materials not listed above: please contact your AZ sales representative.

PT Diagram, PN 16 - PN 100

PTFE sleeved plug valves



Body material

- EN 10213 - 1.0619 / Carbon Steel
 - EN 10213 - 1.4408 / Stainless Steel
 - EN 17744 - 2.4819 / Hastelloy
 - EN 17730 - 2.4365 / Monel 400
 - UNS N08007 - 1.4500 / Alloy 20
- other body materials on request

Sleeve material

- PTFE (virgin) / PTFE (glass) T_{max} 230°C / 446°F
 - TFM / NXT / M111 / PTFE graphite T_{max} 250°C / 482°F
 - PTFE-P / NFCE / NCS T_{max} 320°C / 608°F
- other sleeve materials on request

The data given are max. values according to EN 12516-1 and EN 1092-1.

IMPORTANT NOTE


for demanding conditions, such as process temperatures exceeding 200°C / 392°F: Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of sleeve material, cover sealing type and special features.

For temperatures < -29°C / -20°F, ($T_{limit} = -60°C / -76°F$) operating temperature, low-temperature carbon steel or austenitic stainless steels are required.

Subject to technical change without notice.

PT Diagram, Class 150 - Class 600

PTFE sleeved plug valves



Body material

- ASTM A216 - WCB
- ASTM A351 - CF8M
- ASTM A494 - CW12MW / Hastelloy
- ASTM A494 - M35.1 / Monel 400
- ASTM A351 - CN7M Alloy 20
- other body materials on request

Sleeve material

- PTFE (virgin) / PTFE (glass) T_{max} 230°C / 446°F
- TFM / NXT / M111 / PTFE graphite T_{max} 250°C / 482°F
- PTFE-P / NFCE / NCS T_{max} 320°C / 608°F
- other sleeve materials on request

The data given are max. values according to ASME B16.34.

IMPORTANT NOTE


for demanding conditions, such as process temperatures exceeding 200°C / 392°F: Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of sleeve material, cover sealing type and special features.

For temperatures < -29°C / -20°F, ($T_{limit} = -60°C / -76°F$) operating temperature, low-temperature carbon steel or austenitic stainless steels are required.

Subject to technical change without notice.

PT Diagram High Pressure, PN 160

PTFE sleeved plug valves with trunnion mounted design



Body material (in line with EN 12516-1 and EN 1092-1)

- EN 10213 - 1.4408 / Stainless Steel
- other body materials on request

Sleeve material

- PTFE (virgin) / PTFE (glass) T_{max} 230°C / 446°F
- . - . TFM / NXT / M111 / PTFE graphite T_{max} 250°C / 482°F
- PTFE-P / NFCE / NCS T_{max} 320°C / 608°F
- other sleeve materials on request

The data given are max. values according to EN 12516-1 and EN 1092-1.

IMPORTANT NOTE


for demanding conditions, such as process temperatures exceeding 200°C / 392°F: Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of sleeve material, cover sealing type and special features.

For temperatures < -29°C / -20°F, ($T_{limit} = -60°C / -76°F$) operating temperature, low-temperature carbon steel or austenitic stainless steels are required.

Subject to technical change without notice.

PT Diagram High Pressure, Class 900

PTFE sleeved plug valves with trunnion mounted design



Body material (in line with ASME B16.34)

- ASTM A351 - CF8M / Stainless Steel
- ASTM A995 - CD3MN / Superduplex
- other body materials on request

Sleeve material

- ⋯⋯⋯ PTFE (virgin) / PTFE (glass) T_{max} 230°C / 446°F
- - - TFM / NXT / M111 / PTFE graphite T_{max} 250°C / 482°F
- — — PTFE-P / NFCE / NCS T_{max} 320°C / 608°F
- other sleeve materials on request

The data given are max. values according to ASME B16.34.


IMPORTANT NOTE

for demanding conditions, such as process temperatures exceeding 200°C / 392°F: Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of sleeve material, cover sealing type and special features.

Subject to technical change without notice.

For temperatures < -29°C / -20°F, ($T_{limit} = -60°C / -76°F$) operating temperature, low-temperature carbon steel or austenitic stainless steels are required.

PT Diagram, PN 10 - PN 40 lined valves



Body material

- EN 10213 - 1.0619 / Carbon Steel
 - EN 10213 - 1.4408 / Stainless Steel
 - EN 1563 - EN-GJS-400-18-LT / Ductile Iron
- other body materials on request

Lining combination

	Body	Plug / Ball	T _{MAX}
- - -	PFA	PTFE or special*	210°C / 410°F
.	PFA	PFA	200°C / 392°F
- . - . -	all combinations with PFA and FEP		150°C / 302°F
.	PFA conductive	PFA conductive**	125°C / 257°F

*) Special materials (metallic) for plugs without lining on request

**) Material combination PFA / FEP possible

The data given are max. values according to EN 12516-4.


IMPORTANT NOTE

for demanding conditions, such as process temperatures exceeding 150°C / 302°F: Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of lining material, cover sealing type and special features.

Maximum breakaway torque depending on material combinations according to the technical data sheets of the plug valve.

Subject to technical change without notice.

PT Diagramm, Class 150 - Class 300 lined valves



Body material

- ASTM A216 - WCB
- ASTM A351 - CF8M / Stainless Steel
- ASTM A395 / Ductile Iron
- other body materials on request

Lining combination

	Body	Plug / Ball	T _{MAX}
- - -	PFA	PTFE or special*	210°C / 410°F
.	PFA	PFA	200°C / 392°F
- . - . -	all combinations with PFA and FEP		150°C / 302°F
.	PFA conductive	PFA conductive**	125°C / 257°F

*) Special materials (metallic) for plugs without lining on request

***) Material combination PFA / FEP possible

The data given are max. values according to ASME B16.34 / B16.42.

IMPORTANT NOTE

for demanding conditions, such as process temperatures exceeding 150°C / 302°F: Valve size, media phase, plug position & temperature (constant or fluctuating) may have an impact on the lifetime. Consult factory for proper selection of lining material, cover sealing type and special features.

Maximum breakaway torque depending on material combinations according to the technical data sheets of the plug valve.

Subject to technical change without notice.

Plug types: two-way and multi-port for standard reduced and full bore design



- position indicator for all multi-way valves welded on lever or stem extension
- Lined plug valves: multi-way plugs only with PFA / FEP plug lining or made of special materials. Two-way plugs with PTFE lining up to DN 100 / NPS 4 available


Recommendation for three-way valves type F-3-S with vertical outlet (longer life-time compared to type F-3-W with horizontal outlet)

Options

Plugs made of special materials or special designs, e.g. with flushing devices, vent holes in plug bottom or plug upstream / downstream side

2-way	Plug type	Pos. I = 0°	Pos. II = 90°	Pos. III = 180°	Pos. IV = 270°
Type F-2-ISO-STANDARD					

*) For highly expanding media AZ recommends the "i-plug" (relief hole and open plug bottom)



Type F-2-ISO-STANDARD-A

Plug types: 3-way valve for STANDARD and EXTRA design

Plug type	Pos. I = 0°	Pos. II = 90°	Pos. III = 180°	Pos. IV = 270°	3-way (vertical)
L					 Type F-3-S-ISO-STANDARD Type F-3-S-ISO-STANDARD-A
LL					
IL*					
TT					

Plug type	Pos. I = 0°	Pos. II = 90°	Pos. III = 180°	Pos. IV = 270°	3-way (horizontal)
T4					 Type F-3-W-ISO-STANDARD Type F-3-W-ISO-STANDARD-A
L4					

*) for EXTRA valves with IL-plug, F-3-W-EXTRA with T4-plug is recommended (higher flowrate)
 Lined valves: the IL-plug is only available in special materials

Plug types 3-way (120°) valves and 4-way valves for STANDARD and EXTRA design

3-way (120°) type 3-W-120:

- min. cross section guaranteed (switching phase)
- piggable execution on request
- minimum flow guaranteed

transflow design

3-way (120°) type 3-WP-120

- with positive overlap
- flow interruption / isolation

positive overlap

3-way (120°)	Plug type	Pos. I = 0°	Pos. II = 120°	Pos. III = 240°	
	L120 				

4-way	Plug type	Pos. I = 0°	Pos. II = 90°	Pos. III = 180°	Pos. IV = 270°
 Type F-4-ISO-STANDARD 	L4 				
	T4 				
	LL4 				

open
 closed

Plug types 4-way (special) and 5-way valves for STANDARD and EXTRA design

Plug type	Pos. I = 0°	Pos. II = 90°	Pos. III = 180°	Pos. IV = 270°	4-way (special) / 5-way
L	 A, B, C ✓ A-B ✗ C-D-E	 A, B, C ✓ A-E ✗ B-C-D	 A, B, C ✓ A-C ✗ B-D-E	 A, B, C ✓ A-D ✗ B-C-E	 Type F-4-Special-ISO-STANDARD Type F-5-ISO-STANDARD
LL	 A, B, C ✓ A-B-E ✗ C-D	 A, B, C ✓ A-C-E ✗ B-D	 A, B, C ✓ A-C-D ✗ B-E	 A, B, C ✓ A-B-D ✗ C-E	
IL	 A, B, C ✓ A-E + B-C ✗ D	 A, B, C ✓ A-C + D-E ✗ B	 A, B, C ✓ A-D + B-C ✗ E	 A, B, C ✓ A-B + D-E ✗ C	
T	 A, B, C ✓ A-B-C ✗ D-E	 A, B, C ✓ A-D-E ✗ B-C	 A, B, C ✓ A-B-C ✗ D-E	 A, B, C ✓ A-D-E ✗ B-C	
TT	 A, B, C ✓ A-B-C-D ✗ E	 A, B, C ✓ A-B-D-E ✗ C	 A, B, C ✓ A-B-C-E ✗ D	 A, B, C ✓ A-C-D-E ✗ B	

open
 closed



AZ plants

Headquarters Germany

AZ Armaturen GmbH
Waldstrasse 7
D-78087 Moenchweiler
Phone: +49 / 7721 / 7504-0
sales@az-armaturen.com
www.az-armaturen.com

Plant Brazil

AZ Armaturen do Brasil LTDA.
Av. Osvaldo Berto, 600
CEP 13255-405 Itatiba - SP
Phone: +55 / 11 / 452499-50 / -51
az@az-armaturen.com.br
www.az-armaturen.com.br

Plant China

AZ Armaturen (Taicang) Co., Ltd.
No. 1 Zhengzhou Road
215400 Taicang City
Phone: +86 / 512 / 53667600
info@az-armaturen.cn
www.az-armaturen.cn

Plant South Africa

AZ Armaturen South Africa PTY LTD.
28 Derick Coetzee Street
Boksburg 1459
Phone: +27 / 11 / 397 3665
sales@az-armaturen.co.za
www.az-armaturen.co.za

Plant USA

AZ VALVES North America L.P.
18702 Intercontinental Crossing Drive
Houston, TX 77073
Phone: +1 / 832 / 827 2163
sales@azvalves.com
www.azvalves.com

Plant Saudi Arabia

AZ Valves Arabia Manufacturing Co.
Building No. 4066
Street 26, Cross 09
Dammam, Kingdom of Saudi Arabia
Phone: +966 / 13 835 1880
info@azvalves.com.sa

AZ services

Europe

- Germany (Moenchweiler & Rhineland)
- France (Lyon/ Bourg-lès-Valence)
- Great Britain (York/Roecliffe)
- Italy (Milan/Caltignaga)
- Poland (Warsaw/Opoczno)
- The Netherlands (Amsterdam)
- Russia (St. Petersburg)

America

- USA (Houston/TX)
- Brazil (São Paulo, Itatiba & Belem)
- Chile (Santiago de Chile)
- Mexico (Mexico-City)
- Peru (Lima)

Middle East

- Saudi Arabia (Dammam)

Asia

- China (Taicang)
- South Korea
- Thailand (Rayong)
- Vietnam (Hanoi)

Africa

- South Africa (Johannesburg)



Detailed addresses
on our website

www.az-armaturen.com